

	20 in / 510 mm	26 in / 660 mm	28 in / 710 mm	20 in / 510 mm	24 in / 610 mm	26 in / 660 mm
ank Material:	Poly 5/16" (7.9mm)					
hassis Construction:	3/16" Steel (4.8mm) Powder Coated Steel					
ront Wheels (Diameter × Width):	(2×) 8" × 2" (20.3 x 5.1 cm) - Non-Marking Grey					
ear Casters (Diameter × Width):	(2×) 2.5" × 1.38" (6.4 x 3.5cm) - Non-Marking Grey					
ength x Width x Height mensions listed are for the largest width deck infiguration and squeegees removed from the machine	53 x 29 x 38.5 in* 135 x 74 x 98 cm*					
crub Motor(s):	0.75 hp / 559 watts 1.5 hp / 1,100 watts 0.7					0.75 hp / 559 watts
ısh RPM:	270 rpm 2,500 rpm				270 rpm	
stem Voltage:	24 VDC					
andard Battery:	150 ah WET					
ttery Run Time (Up to Hours):*	3					
narger:	120VAC / 60 Hz Input - 24VDC / 12 amp Output					
action Drive System:	0.5hp - All Gear / Sealed (373 watts)					
lution Tank Capacity:	16 gal / 61 L					
olution Flow / Filter:	0 - 0.6 GPM / Stainless Inline (0 - 2.3 LPM)					
ecovery Tank Capacity:	16 gal / 61 L					
cuum Motor:	0.8 hp / 36V / 3 Stage / 640 watts					
acuum Water Lift:	70" / 178 cm / 70 cfm					
ound Levels:**	66 dBA**					
Productivity - Theoretical:***	20,000 ft2/hr	25,979 ft2/hr	28,000 ft2/hr	24,000 ft2/hr	28,000 ft2/hr	24,000 ft2/hr
	1,858 m2/hr	2,414 m2/hr	2,601 m2/hr	2,230 m2/hr	2,601 m2/hr	2,230 m2/hr
Productivity - Practical:***	9,274 ft2/hr	12,061 ft2/hr	13,000 ft2/hr	11,143 ft2/hr	13,000 ft2/hr	11,143 ft2/hr
	862 m2/hr	1,121 m2/hr	1,208 m2/hr	1,035 m2/hr	1,208 m2/hr	1,035 m2/hr



Location:
Timberline Cleaning Equipment
1711 South Street
Racine, WI
53404

Phone: 262-833-4040 877-401-0730 Website: www.timberlineclean.com

Email: customerservice@timberlineclean.com

*Battery Run Times are based on continuous scrubbing run times, standard batteries, low down pressure and all options off.

**Decibel levels for Disk per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

***Productivity is based off of ISSA 2010 Cleaning Times