





XS Compact Scrubbers			XS Standard Scrubbers		
SINGLE DISK		SINGLE DISK		ORBITAL	
					
17 in / 430 mm		20 in / 510 mm		20 in / 510 mm	
Tank Material:			Poly 5/16" (1.9 mm)		
Chassis Construction:			1/8" Steel (3.2 mm) Powder Coated Steel		
Rear Wheels (Diameter x Width):			(2x) 8" x 2" (2x) 20.3 x 5.1 cm - Non-Marking Grey		
Front Casters (Diameter x Width):			(2x) 2.5" x 1.38" (2x) 6.4 x 3.5 cm - Non-Marking Grey		
Length x Width x Height		35 x 18 x 38 in 89 x 46 x 97 cm		42 x 21 x 39 in 107 x 53 x 99 cm	
Scrub Motor:			0.75 hp / 559 watts		1.0 hp / 745 watts
Brush RPM:			200 rpm		2500 rpm
System Voltage:			24 VDC		
Standard Battery:			95 ah WET		
Battery Run Time (Up to Hours):*			2.5		
Charger:			120VAC / 60 Hz Input - 24VDC / 8 amp Output		
Brush Drive System:			Pad Assist - Only Pad Assist Models		
Traction Drive System:			0.5hp - All Gear / Sealed (373 watts) - Only Traction Models		
Solution Tank Capacity:			10 gal / 38 L		
Solution Flow / Filter:			0 - 0.5 GPM / Stainless Inline (0 - 1.9 LPM)		
Recovery Tank Capacity:			10 gal / 38 L		
Vacuum Motor:			0.8 hp / 36V / 3 Stage / 640 watts		
Vacuum Water Lift:			70" / 178 cm / 70 cfm		
Squeegee:		30 in (76 cm)	34 in (86 cm)	30 in (76 cm)	34 in (86 cm)
Sound Levels:**			66 dBA**		
Productivity Brush Drive - Theoretical:***		12,739 ft2/hr 1,183 m2/hr	15,748 ft2/hr 1,463 m2/hr	12,739 ft2/hr 1,183 m2/hr	15,748 ft2/hr 1,463 m2/hr
Productivity Brush Drive - Practical:***		5,917 ft2/hr 550 m2/hr	7,308 ft2/hr 679 m2/hr	5,917 ft2/hr 550 m2/hr	7,308 ft2/hr 679 m2/hr
Productivity Traction - Theoretical:***		16,970 ft2/hr 1,577 m2/hr	20,000 ft2/hr 1,858 m2/hr	16,970 ft2/hr 1,577 m2/hr	20,000 ft2/hr 1,858 m2/hr
Productivity Traction - Practical:***		7,886 ft2/hr 733 m2/hr	9,274 ft2/hr 862 m2/hr	7,886 ft2/hr 733 m2/hr	9,274 ft2/hr 862 m2/hr



**Location:**  
Timberline Cleaning Equipment  
1711 South Street  
Racine, WI  
53404

**Phone:**  
262-833-4040  
877-401-0730

**Email:**  
[customerservice@timberlineclean.com](mailto:customerservice@timberlineclean.com)

**Website:**  
[www.timberlineclean.com](http://www.timberlineclean.com)

Specifications subject to change without notice.  
\*Battery Run Times are based on continuous scrubbing run times, standard batteries, low squee pressure and all options off.  
\*\*Decibel levels for Disk per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA.

\*\*\*Productivity is based off of ISSA 2010 Cleaning Times