

## M - Series Scrubbers

	SINGLE DISK	DUAL DISK		ORBITAL	ORBITAL	CYLINDRICAL	
							
	<b>20 in / 510 mm</b>	<b>26 in / 660 mm</b>	<b>28 in / 710 mm</b>	<b>20 in / 510 mm</b>	<b>24 in / 610 mm</b>	<b>28 in / 711 mm</b>	
				<b>20 in / 510 mm</b>		<b>26 in / 660 mm</b>	
Tank Material:	Poly 5116* (7.8mm)						
Chassis Construction:	3/16" Steel (4.8mm) Powder Coated Steel						
Front Wheels (Diameter x Width):	(2x) 8" x 2" (20.3 x 5.1 cm) - Non-Marking Grey						
Rear Casters (Diameter x Width):	(2x) 2.5" x 1.38" (6.4 x 3.5cm) - Non-Marking Grey						
Length x Width x Height:	53 x 29 x 38.5 in*						
Dimensions listed are for the largest width deck configuration and spaces removed from the machine.							
Scrub Motor(s):	0.75 hp / 559 watts		270 rpm		1.5 hp / 1,100 watts		
Brush RPM:	180 rpm			2,500 rpm			
System Voltage:	24 VDC						
Standard Battery:	150 ah WET						
Battery Run Time:**	Up to 3 Hours						
Charger:	120VAC / 60 Hz Input - 24VDC / 12 amp Output						
Traction Drive System:	0.5hp - All Gear / Sealed (373 watts)						
Solution Tank Capacity:	16 gal / 61 L						
Solution Flow / Filter:	0 - 0.6 GPM / Stainless Inline (Ø - 2.3 LPM)						
Recovery Tank Capacity:	16 gal / 61 L						
Vacuum Motor:	0.8 hp / 36V / 3 Stage / 640 watts						
Vacuum Water Lift:	70" / 178 cm / 70 cfm						
Squeegee:	33 in (84 cm)	37 in (94 cm)		33 in (84 cm)	37 in (94 cm)		
Sound Levels:**	66 dBA**						
Productivity - Theoretical***	20,000 ft <sup>2</sup> /hr 1,858 m <sup>2</sup> /hr	25,979 ft <sup>2</sup> /hr 2,414 m <sup>2</sup> /hr	28,000 ft <sup>2</sup> /hr 2,601 m <sup>2</sup> /hr	24,000 ft <sup>2</sup> /hr 2,230 m <sup>2</sup> /hr	28,000 ft <sup>2</sup> /hr 2,601 m <sup>2</sup> /hr	28,000 ft <sup>2</sup> /hr 2,601 m <sup>2</sup> /hr	27,027 ft <sup>2</sup> /hr 2,510 m <sup>2</sup> /hr
Productivity - Practical***	9,274 ft <sup>2</sup> /hr 862 m <sup>2</sup> /hr	12,061 ft <sup>2</sup> /hr 1,121 m <sup>2</sup> /hr	13,000 ft <sup>2</sup> /hr 1,208 m <sup>2</sup> /hr	11,143 ft <sup>2</sup> /hr 1,035 m <sup>2</sup> /hr	13,000 ft <sup>2</sup> /hr 1,208 m <sup>2</sup> /hr	13,000 ft <sup>2</sup> /hr 1,208 m <sup>2</sup> /hr	12,526 ft <sup>2</sup> /hr 1,163 m <sup>2</sup> /hr



**Location:**  
Timberline Cleaning Equipment  
1711 South Street  
Racine, WI  
53404

**Phone:**  
262-833-4040  
877-401-0730

**Website:**  
[www.timberlineclean.com](http://www.timberlineclean.com)

**Email:**  
[customerservice@timberlineclean.com](mailto:customerservice@timberlineclean.com)

\*Battery Run Times are based on continuous scrubbing on a smooth, level surface. Actual run times may vary based on floor conditions, load, and operator technique. Specifications subject to change without notice. \*\*Sound Levels are based on ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & CGA. \*\*\*Productivity is based off of ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & CGA.